




# KEPNER PRODUCTS COMPANY

ESTABLISHED IN 1948


Part Numbers: Kep-O-seal® Relief Check Valve Fixed Settings 1/8" to 2" sizes

## PORT CONFIGURATIONS


19 IJIC - IJIC




7 JIC - MPT




17 JIC - IJIC




5 MPT - JIC



15 IJIC - JIC




4 FPT - FPT




13 JIC - JIC




3 MPT - MPT




11 JIC - FPT




2 FPT - MPT



9 FPT - JIC



1 MPT - FPT



## PART NUMBER EXAMPLE

**4 06 - C - 3 - 25**

## PORT SIZES

04 = 1/8 PIPE - 1/4 TUBE

16 = 1" PIPE - 1" TUBE

06 = 1/4 PIPE - 3/8 TUBE

20 = 1 1/4 PIPE - 1 1/4 TUBE

08 = 3/8 PIPE - 1/2 TUBE

24 = 1 1/2 PIPE - 1 1/2 TUBE

10 = 1/2 PIPE - 5/8 TUBE

32 = 2" PIPE - 2" TUBE

12 = 3/4 PIPE - 3/4 TUBE

## CONSTRUCTION MATERIALS

A = ALUMINUM

D = 303 STAINLESS STEEL

B = BRASS

F = 316 STAINLESS STEEL

C = STEEL

## O-RING SEALS

1 = BUNA-N

3 = TEFLON®

9 = NEOPRENE

18 = VITON®

25 = ETHYLENE PROPYLENE

## CRACK PRESSURE

Substitute desired crack pressure value for - XX

5 = 5 PSI CRACK

10 = 10 PSI CRACK

25 = 25 PSI CRACK

50 = 50 PSI CRACK

65 = 65 PSI CRACK

OTHERS AVAILABLE

Valve performance is dependent on proper selection, application, installation and maintenance. Consult Factory.  
Kepner Products Company, Villa Park, IL 630.279.1550 E-mail: [kepner@kepner.com](mailto:kepner@kepner.com)