




KEPNER PRODUCTS COMPANY

ESTABLISHED IN 1948

INNOVATIVE ZERO LEAKAGE CONTROL VALVES FOR LIQUID AND GAS

Our unique *Flexible Seal Seat*[™] assures bubble-tight performance.

The Kepner *Flexible Seal Seat*[™] design offers positive leakage control of liquid or gas. The seat design is a carefully engineered combination of metal-to-metal and resilient O-Ring seal contact. The O-Ring is securely retained at the seat rather than on the poppet, protecting it from the destructive abrading and blasting effect of the flow; seal life is extended. Seat "wire drawing" common to conventional valves has been eliminated by the *Flexible Seal Seat*[™] design. The seal closes around scratches, dents, and other irregularities and effectively prevents any leakage past the seat. A wide choice of O-Ring seal elastomers is offered for system compatibility. The *Flexible Seal Seat*[™] design is available in check, relief, shuttle, and pilot operated check valves, and has been successfully applied to millions of fluid control situations.



CLOSED: (No Flow) Relaxed O-Ring seal and gentle seal-to-poppet contact guarantees low pressure sealing and eliminates valve chatter.


OPEN: (Full Flow) Seal flexes to close off all external leakage around end cap. Enclosure protects O-Ring seal, prevents seal displacement.

CLOSED: (Reverse Checked) Seal still holding external leakage now also flexes around poppet. Higher pressures tighten the seal. Bubble-tight shutoff.

◆ LEAK TIGHT SEALING

◆ POSITIVE ACTION EVEN AT LOW PRESSURE

◆ FREEDOM FROM CHATTER



KEPNER PRODUCTS COMPANY

995 N. Ellsworth Avenue, Villa Park, Illinois 60181

Telephone: 630.279.1550 FAX: 630.279.9669 E-mail: kepner@kepner.com